

The HEP-PAPER package*

Publications in high energy physics

Jan Hajer[†]

2026/08/01

Abstract

The HEP-PAPER package is the aggregate publication setup for the HEP package suite. It configures the page geometry, language, fonts, hyperlinks, title data, bibliography, acronyms, references, floats, text helpers, and math fonts by loading the corresponding modular packages with publication-oriented defaults.

Contents

1	Introduction	2
1.1	Options	2
1.1.1	Deactivation	2
1.1.2	Compatibility	3
1.1.3	Reactivation	3
2	Macros and environments	3
2.1	Title page	3
2.2	Text	4
2.2.1	References and footnotes	4
2.2.2	Acronyms	4
2.3	Math	4
2.4	Floats	5
2.5	Bibliography	5
3	Conclusion	6

*This document corresponds to HEP-PAPER v2.5.

[†]jan.hajer@tecnico.ulisboa.pt

1 Introduction

For usual publications it is enough to load additionally to the `article` class without optional arguments only the HEP-PAPER package [1].

```
\documentclass{article}
\usepackage{hep-paper}
```

The most notable changes after loading the HEP-PAPER package are the changes of some L^AT_EX defaults. The paper and font sizes are set to A4 and 11 pt, respectively. Additionally, the paper geometry is adjusted using the GEOMETRY package [2]. Furthermore, text and math fonts are configured with HEP-FONT and HEP-MATH-FONT, text helpers with HEP-TEXT, bibliographies with HEP-BIBLIOGRAPHY, acronyms with HEP-ACRONYM, references and hyperlinks with HEP-REFERENCE, titles with HEP-TITLE, and floats with HEP-FLOAT.

1.1 Options

- paper** The `paper=format` option loads the specified paper format. The possible *formats* are: `a0`, `a1`, `a2`, `a3`, `a4`, `a5`, `a6`, `b0`, `b1`, `b2`, `b3`, `b4`, `b5`, `b6`, `c0`, `c1`, `c2`, `c3`, `c4`, `c5`, `c6`, `ansia`, `ansib`, `ansic`, `ansid`, `ansie`, `letter`, `executive`, `legal`. The default is `a4`.
- font** The `font=size` option loads the specified font size. The possible *sizes* are: `8pt`, `9pt`, `10pt`, `11pt`, `12pt`, `14pt`, `17pt`, `20pt`. The default is `11pt`.
- lang** The `lang=name` option switches the document language. The default is `british`.
- sansserif** The `sansserif` option switches the document including math to sans serif font shape.
- oldstyle** The `oldstyle` option activates the use of oldstyle text- (123) in favour of lining- (123) figures in text mode.
- parskip** The `parskip` option changes how paragraphs are separated from each other using the PARSKIP package [3]. The L^AT_EX default is separation via indentation the `parskip` option switches to separation via vertical space.¹
- symbols** The `symbols=family` is passed to the HEP-MATH-FONT package [4] and sets the family of the symbol fonts. `symbols=false` deactivates loading any additional symbol fonts.

1.1.1 Deactivation

The HEP-PAPER package loads few bigger packages which have a large impact on the document. The deactivation options can prevent such and other adjustments.

- defaults** The `defaults` option prevents the adjustment of the page geometry and the font size set by the document class.
- title** The `title=false` option deactivates the title page adjustments.
- bibliography** The `bibliography=key` option prevents the automatic loading of the HEP-BIBLIOGRAPHY package [5] if *key*=`false`.
- glossaries** The `glossaries=false` option deactivates acronyms and the use of the HEP-ACRONYM package [6].
- references** The `references=false` option prevents the CLEVEREF package [7] from being loaded and deactivates further redefinitions of reference macros.

¹ Although the `parskip` option is used for this document, it is recommended only for very few document types such as technical manuals or answers to referees.

1.1.2 Compatibility

The compatibility options activate the compatibility mode for certain classes and packages used for publications in high energy physics. They are mostly suitable combinations of options described in the previous section. If HEP-PAPER is able to detect the presence of such a class or package, i.e. if it is loaded before the HEP-PAPER package, the compatibility mode is activated automatically.

- `beamer` The `beamer` option activates the BEAMER [8] compatibility mode.
- `jhep` The `jhep` option activates the JHEP [9] compatibility mode.
- `jcap` The `jcap` option activates the JCAP [10] compatibility mode.
- `revtex` The `revtex` option activates the REVTeX [11] compatibility mode.
- `pos` The `pos` option activates the PoS compatibility mode.
- `springer` The `springer` option activates the compatibility mode the `svjour` class [12].

1.1.3 Reactivation

The HEP-PAPER package deactivates unrecommended macros, which can be reactivated manually.

- `manualplacement` The `manualplacement` option reactivates manual float placement.
- `eqnarray` The `eqnarray` option reactivates the depreciated `eqnarray` environment.

2 Macros and environments

- `twocolumn` If the global `twocolumn` option is present the page geometry is changed to cover almost the entire page. Additionally the `abstract*` environment is defined that generates a one column abstract and takes care of placing the title information.

2.1 Title page

- `\series` The `\series{<series>}` macro is defined using the HEP-TITLE package [13].
- `\title` The portable document format (PDF) meta information is set according to the `\title{<text>}` and `\author{<text>}` information.
- `\subtitle` The `\subtitle{<subtitle>}` macro is defined.
- `\editor` The following lines add e.g. two authors with different affiliations
 - `\author` `\author[1]{Author one \email{email one}}`
 - `\affiliation` `\affiliation[1]{Affiliation one}`
 - `\author` `\author[2]{Author two \email{email two}}`
 - `\email` `\affiliation[1,2]{Affiliation two}`
- `\preprint` The `\preprint{<number>}` macro places a pre-print number in the upper right corner of the title page.
- `abstract (env.)` The `abstract` environment is adjusted to not start with an indentation.
- `\titlefont` Various title font macros are defined, allowing to change the appearance of the `\maketitle` output.
- `\subtitlefont`
- `\authorfont`
- `\affiliationfont`
- `\preprintfont`

2.2 Text

<code>\inlinelist</code>	The <code>\inlinelist</code> and <code>\enumdescript</code> environments are defined.
<code>\enumdescript</code>	A bold versions SMALL CAPS and a sans serif version of SMALL CAPS is provided.
<code>\textsc</code>	The <code>\underline</code> macro is redefined to allow line-breaks. The <code>\overline</code> macro is extended to
<code>\underline</code>	also overline text outside of math environments.
<code>\overline</code>	If the <code>\parskip</code> option is activated the <code>\useparindent</code> macro switches to the usual <code>\parindent</code>
<code>\useparskip</code>	mode, while the <code>\useparskip</code> macro switches to the <code>\parskip</code> mode.
<code>\useparindent</code>	2.2.1 References and footnotes
<code>\cref</code>	References are extended with the <code>CLEVEREF</code> package [7], which allows to e.g. just type <code>\cref{<key>}</code> in order to write ‘figure 1’. Furthermore, the <code>CLEVEREF</code> package allows to reference multiple objects within one <code>\cref{<key1,<key2>}</code> .
<code>\cite</code>	Citations are adjusted to not start on a new line in order to avoid the repeated use of <code>~\cite{<key>}</code> .
<code>\ref</code>	References are also adjusted to not start on a new line.
<code>\eqref</code>	Footnotes are adjusted to swallow white space before the footnote mark and at the beginning of
<code>\subref</code>	the footnote text.
<code>\footnote</code>	2.2.2 Acronyms
<code>\acronym</code>	The <code>HEP-ACRONYM</code> package [6] is loaded. The <code>\acronym{<*>[<typeset abbreviation>]{<abbreviation>}{<*>}{<definition>}}</code>
<code>\shortacronym</code>	<code>definition]</code> macro generates the singular <code>\<abbreviation></code> and plural <code>\<abbreviation>s</code> macros. The
<code>\longacronym</code>	first star prevents the addition of an ‘s’ to the abbreviation plural. The second star restores the $\TeX$ default of swallowing subsequent white space. The long form is only shown at the first appearance of these macros, later appearances generate the abbreviation with a hyperlink to the long form. The long form is never used in math mode. Capitalization at the beginning of paragraphs and sentences is (mostly) ensured. The <code>\shortacronym</code> and <code>\longacronym</code> macros are drop-in replacements of the <code>\acronym</code> macro showing only the short or long form of their acronym.

2.3 Math

<code>\mathbf</code>	The <code>HEP-MATH</code> [14] and <code>HEP-MATH-FONT</code> [4] packages are loaded. Bold math, via <code>\mathbf</code> is improved, i.e. ($Ab\Gamma\delta\mathbf{Ab}\Gamma\delta$). Macros switching to <code>\bfseries</code> such as <code>\section{<text>}</code> are
<code>\text</code>	ensured to also typeset math in bold. The <code>\text{<text>}</code> macro makes it possible to write text
<code>\mathsf</code>	within math mode, i.e. ($Ab\Gamma\delta\mathbf{Ab}\Gamma\delta$). The math sans serif alphabet is redefined to be italic sans
<code>\mathscr</code>	serif if the main text is serif and italic serif if the main text is sans serif, i.e. ($Ab\Gamma\delta\mathbf{Ab}\Gamma\delta$). The
<code>\mathbb</code>	<code>\mathcal</code> font i.e. ($\mathcal{ABCD}$) is accompanied by the <code>\mathscr</code> font i.e. ($\mathscr{ABCD}$). The <code>\mathbb</code>
<code>\mathfrak</code>	font is adjusted depending on the <code>\sansserif</code> option i.e. ($\mathbb{h}1$). Finally, the <code>\mathfrak</code> font is
<code>\nicefrac</code>	also available i.e. ($\mathfrak{AaBb12}$).
<code>\textfrac</code>	The <code>\frac{<number>}{<number>}</code> macro is accompanied by <code>\nicefrac{<number>}{<number>}</code> ,
<code>\flatfrac</code>	<code>\textfrac{<number>}{<number>}</code> , and <code>\flatfrac{<number>}{<number>}</code> leading to $\frac{1}{2}$, $\frac{1}{2}$, $\frac{1}{2}$,
<code>\diag</code>	and $\frac{1}{2}$. Diagonal matrix <code>\diag</code> and signum <code>\sgn</code> operators are defined.
<code>\mathdef</code>	The <code>\mathdef{<name>}[<arguments>]{<code>}</code> macro (re-)defines macros only within math mode
<code>\diag</code>	without changing the text mode definition.
<code>\sgn</code>	
<code>\mathdef</code>	

`\i` The imaginary unit i and the differential d are defined using this functionality.

`\d` For longer paper it can be useful to re-number the equation in accordance with the section numbering `\numberwithin{equation}{section}`. In order to further reduce the size of equation counter it can be useful to wrap `align` environments with multiple rows in a `subequations` environment.

`\unit` The correct spacing for units, cf. equation (2.1), is provided by the macro `\unit[⟨value⟩]{⟨unit⟩}` which can also be used in text mode. The macro `\inv[⟨power⟩]{⟨text⟩}` allows to avoid math mode also for inverse units such as 5 fb^{-1} typeset via `\unit[5]{\inv{fb}}`.

`\inv`

Greek letters are adjusted to always be italic and upright in math and text mode, respectively, using the HEP-MATH-FONT [4] package. This allows differentiations like

$$\sigma = 5\text{ fb} , \quad \text{at } 5\sigma \text{ C.L.} , \quad \mu = 5\text{ cm} , \quad l = 5\mu\text{m} . \quad (2.1)$$

Additionally, Greek letters can also be directly typed using Unicode.

`\ev` The HEP-MATH package [14] provides additional macros such as

`\pdv`

`\comm` $\langle\phi\rangle$, $\frac{\partial^3 f}{\partial x \partial y^2}$, $[A, B]$, $\mathcal{O}(x^2)$, $x|_0^\infty$, $\det(M)$. (2.2)

`\order`

`\cancel` The `\cancel{⟨characters⟩}` macro and the `\slashed{⟨character⟩}` macro allow to ~~cancel~~ math and use the Dirac slash notation i.e. $\cancel{\phi}$, respectively.

`\slashed`

`\overlefttrightarrow` A better looking over left right arrow is defined i.e. $\overleftrightarrow{\partial}$.

2.4 Floats

`figure (env.)` Automatic float placement is adjusted to place a single float at the top of pages and to reduce the number of float pages, using the HEP-FLOAT package [15]. The most useful float placement is usually achieved by placing the float *in front* of the paragraph it is referenced in first.

`table (env.)`

`panels (env.)` The `panels` environment provides sub-floats and takes as mandatory argument either the number of sub-floats (default 2) or the width of the first sub-float as fraction of the `\linewidth`. Within the `\begin{panels}[⟨vertical alignment⟩]{⟨width⟩}` environment the `\panel` macro initiates a new sub-float. In the case that the width of the first sub-float has been given as an optional argument to the `panels` environment the `\panel{⟨width⟩}` macro takes the width of the next sub-float as mandatory argument.

`\panel`

`\graphic` The `\graphic[⟨width⟩]{⟨figure⟩}` macro is defined, which is a wrapper for the `\includegraphics{⟨figure⟩}` macro and takes the figure width as fraction of the `\linewidth` as optional argument (default 1).

`\graphics` If the graphics are located in a sub-folder its path can be indicated by `\graphics{⟨subfolder⟩}`.

2.5 Bibliography

`\bibliography` The BIBLATEX package [16] is loaded for bibliography management. The user has to add the line `\bibliography{⟨my.bib⟩}` to the preamble of the document and `\printbibliography` at the end of the document. The bibliography is generated by BIBER [17]. BIBLATEX is extended by the HEP-BIBLIOGRAPHY package [5] to be able to cope with the `collaboration` and `reportNumber` fields provided by inspirehep.net and a bug in the volume number is fixed. Additionally, the PubMed IDs are recognized and ctan.org, github.com, gitlab.com, bitbucket.org, launchpad.net, sourceforge.net, and hepforge.org are valid `eprinttypes`. Errata can be included using the

`\printbibliography`

`erratum`

```

related feature.
\article{key1,
  ...,
  relatedtype="erratum",
  related="key2",
}
\article{key2,
  ...,
}

```

3 Conclusion

The HEP-PAPER package provides a matching selection of preloaded packages and additional macros enabling the user to focus on the content instead of the layout by reducing the amount of manual tasks. The majority of the loaded packages are fairly lightweight, the others can be deactivated with package options.

arxiv-collector [arxiv.org](#) [18] requires the setup dependent `bb1` files instead of the original `bib` files, which causes trouble if the local $\text{\LaTeX}$ version differs from the one used by arXiv. The `ARXIV-COLLECTOR` python script [19] alleviates this problem by collecting all files necessary for publication on arXiv (including figures).

References

- [1] J. Hajer. ‘The `hep-paper` package: Publications in high energy physics’ (2019). CTAN: `hep-paper`. DOI: 10.5281/zenodo.3606436. GitHub: [janhajer/hep-paper](#).
- [2] D. Carlisle and H. Umeki. ‘The `geometry` package: Flexible and complete interface to document dimensions’ (1996). CTAN: `geometry`. GitHub: [davidcarlisle/geometry](#).
- [3] R. Fairbairns, F. Mittelbach, and H. Partl. ‘The `parskip` package: Layout with zero `\parindent`, non-zero `\parskip`’ (1989). CTAN: `parskip`. GitHub: [FrankMittelbach/fmitex](#).
- [4] J. Hajer. ‘The `hep-math-font` package: Extended Greek and sans serif math’ (2021). CTAN: `hep-math-font`. DOI: 10.5281/zenodo.3606436. GitHub: [janhajer/hep-paper](#).
- [5] J. Hajer. ‘The `hep-bibliography` package: Bibliographies for high energy physics’ (2021). CTAN: `hep-bibliography`. DOI: 10.5281/zenodo.3606436. GitHub: [janhajer/hep-paper](#).
- [6] J. Hajer. ‘The `hep-acronym` package: An acronym extension for glossaries’ (2021). CTAN: `hep-acronym`. DOI: 10.5281/zenodo.3606436. GitHub: [janhajer/hep-paper](#).
- [7] T. Cubitt. ‘The `cleveref` package: Intelligent cross-referencing’ (2006). CTAN: `cleveref`. URL: [dr-qubit.org/cleveref](#).
- [8] T. Tantau, J. Wright, and V. Miletić. ‘The `beamer` class: A $\text{\LaTeX}$ class for producing presentations and slides’ (2003). CTAN: `beamer`. GitHub: [josephwright/beamer](#).
- [9] *SISSA Medialab*. ‘The `JHEP` package’ (1997). URL: [jhep.sissa.it/jhep/help/JHEP_TeXclass.jsp](#).
- [10] *SISSA Medialab*. ‘The `JCAP` package’ (2002). URL: [jcap.sissa.it/jcap/help/JCAP_TeXclass.jsp](#).
- [11] *American Physical Society*. ‘The `REVTeX` class: Styles for various Physics Journals’ (1999). CTAN: `revtex`. URL: [journals.aps.org/revtex](#).
- [12] *Springer Verlag*. ‘The `svjour` package: Macros for Springer journals’ (1997). CTAN: `springer`.

- [13] J. Hajer. ‘The `hep-title` package: Extensions for the title page’ (2021). CTAN: `hep-title`. DOI: 10.5281/zenodo.3606436. GitHub: `janhajer/hep-paper`.
- [14] J. Hajer. ‘The `hep-math` package: Extended math macros’ (2021). CTAN: `hep-math`. DOI: 10.5281/zenodo.3606436. GitHub: `janhajer/hep-paper`.
- [15] J. Hajer. ‘The `hep-float` package: Convenience package for float placement’ (2021). CTAN: `hep-float`. DOI: 10.5281/zenodo.3606436. GitHub: `janhajer/hep-paper`.
- [16] P. Lehman, J. Wright, A. Boruvka, and P. Kime. ‘The `biblatex` Package: Sophisticated Bibliographies in $\text{\LaTeX}$ ’ (2006). CTAN: `biblatex`. GitHub: `plk/biblatex`.
- [17] F. Charette and P. Kime. ‘biber: Backend processor for Bib $\text{\LaTeX}$ ’ (2009). GitHub: `plk/biber`. SourceForge: `biblatex-biber`.
- [18] *arXiv Team*. ‘arXiv: free distribution service and an open archive for scholarly articles’ (1991). URL: `arxiv.org`.
- [19] D. Sutherland. ‘`arxiv-collector`: A little Python script to collect $\text{\LaTeX}$ sources for upload to the arXiv’ (2018). GitHub: `dougalsutherland/arxiv-collector`.